



Product data sheet

Triflex Quartz

Use

Light coloured, naturally rounded aggregate used in Triflex systems to provide a hard wearing anti-skid finish, as a key in primers and as a bulk filler.

Properties

- Hard wearing
- Washed, dried and dedusted
- Subject to electro magnetic separation to minimise FE content
- Specific Gravity g/cm³ approx. 2.7⁽¹⁾
- Hardness (Mohs) approx. 7.2⁽¹⁾
- Polished Stone Value (PSV) approx. 57⁽¹⁾

⁽¹⁾As a natural product the figures provided are indicative only and do not constitute a specification



Components

Component	Product
Aggregate	Triflex Quartz

Packaging

Quartz size	Packaging
Triflex Quartz 0.3 - 0.6mm	25.00Kg
Triflex Quartz 0.4 - 0.8mm	25.00Kg
Triflex Quartz 0.4 - 1.2mm	25.00Kg
Triflex Quartz 0.7 - 1.2mm	25.00Kg

Colour(s)

Buff / grey.

Consumption

Refer to Triflex specification and product data sheets.

Storage

Store in a dry area.

Health and safety

Refer to Safety Data Sheets.

Disposal information

Refer to Safety Data Sheets for recommended EWC waste codes.

Notes

The advice we provide on the application of our products is based on extensive development work and many years of experience, and is given to the best of our knowledge. The wide variety of requirements for a building under the most diverse conditions mean that it is necessary for the contractor to test the product for suitability in each case. Triflex reserve the right to make alterations in keeping with technical developments or improvements.

Non-Triflex products must not be used with Triflex systems.

Only the most recent version of this data sheet is valid.