System overview Triflex ProDrain

Specialist vented solution for saturated and contaminated substrates

When a balcony, walkway or terrace has a saturated or contaminated substrate or features a failing buried membrane, it is not possible to successfully overlay these areas with a new waterproofing and surfacing system. In these instances, it is usually necessary to completely remove the existing substrate before refurbishment can begin, which is not only time consuming and costly but also causes disruption. This doesn't always need to be the case, as we have developed a specialist solution which can directly overlay these areas without removal of the existing substrate. Triflex ProDrain offers a safe, clean solution featuring a self-supporting isolating and venting sheet that enables the subsequent Triflex ProTerra waterproofing and surfacing system to be applied over it. It is ultra fast curing and cold liquid applied, allowing installation to be completed quickly, without the use of hot works, and with minimal impact on users. Available in four unique surface finishes, the completed solution also looks good and allows you to completely tailor the colour, texture and finish of your project.



System highlights

Ultimate refurbishment solution

With Triflex ProDrain there is no need for the time consuming and costly removal of the existing substrate, even when it is saturated, contaminated or cracked. The installation of the unique self-supporting decoupling membrane enables the subsequent Triflex ProTerra waterproofing and surfacing system to be applied directly on top, and the thin layer build-up has minimal impact on thresholds. A safe, effective refurbishment solution that lasts.

Fast curing and rapid installation

Traditional refurbishments can take weeks to complete and are susceptible to further water ingress when the existing substrate is removed. Fast curing and easy to install, the entire solution can be installed in just a few days, allowing building to remain occupied during installation, limiting access restrictions and uncessary disruptions to everyday life.

Cold applied system

There is no risk from hot works during installaltion as all our materials are applied in a totally cold liquid form, curing to create a solution that lasts.

Tough and durable protection

The demands of the walkway, balcony and terrace environment are no issue for TriflexProDrain. The system is unaffected by ponding water and resistant to chlorides (salts), carbon dioxide ingress, and approved de-icing and cleaning products. Protection that's built to last, with a low lifecycle cost.

Safety and environmental

Our solvent and isocyanate free resin technology has been assessed under BREEAM principles and can contribute to A+ ratings.

Versatile design

Available in four surface finishes, choose the perfect colour, texture and finish for your project - refer to Triflex colour card.

Application areas

- External walkways, balconies, terraces, pedestrian bridges and other
- pedestrian trafficked areas with saturated or contaminated substratesExternal walkways, balconies, terraces, pedestrian bridges and other
- pedestrian trafficked areas with buried membranes

Compatible substrates

Cementitious substrates

Suitable constructions

• Cast in situ concrete

- Permanent formwork with in situ concrete
- Precast concrete planks with or without structural topping
- Precast double tee units with or without structural topping
- Steel / galvanised steel / structural plastic / timber constructions
- Insulated / warm deck build-ups

Approvals

Approvals (Triflex ProTerra waterproofing and surfacing system)

Fully certified to the highest UK and European standards and classifications, including:



BBA certified - Certificate 13/5051 Product sheet 3

Durability: Under normal service conditions the system will have a service life of at least 15 years



EN 1504-2 certified (full system - large quartz): B3.2 (-20°C) dynamic crack bridging

ETAG 005 certified (reinforced waterproofing membrane) 25 year expected working life




Root and rhizome resistant (reinforced waterproofing membrane): FLL Certified: Root and rhizome resistant

- Fire performance:
- EN ISO-11925-2
- EN ISO-9239-1
- EN 13501-1
- NHBC accepted

Manufacturer certification

- ISO 9001 Quality Management
- ISO 14001 Environmental Management
- ISO 50001 Energy Management

System build-up and consumptions



Layer	Product	Consumption ⁽¹⁾	Aggregate / Broadcast	Overcoat / traffic ⁽²⁾
• Primer (if required)	Triflex ProDrain Primer	0.15l/m ²	-	1 hour
Decoupling membrane	Triflex ProDrain Fix+ DC-MAT Decoupling Membrane	Adhesive: 4.00Kg/m ² minimum Membrane: 1.00m ² /m ²	-	1 hour
Load Ø distribution layer	Triflex Cryl Primer 276	2x 0.55Kg/m ² per application	-	45 minutes per application
 Waterproofing and surfacing system 	Available in four surface finishes - refer to relevant Triflex ProTerra system overview: • Triflex ProTerra Quartz Design • Triflex ProTerra Colour Design • Triflex ProTerra Chips Design • Triflex ProTerra Stope Design			

Triflex ProTerra Stone Design

⁽¹⁾ Minimum consumption assuming a smooth, even, non-absorbent substrate.

 $^{(2)}$ The times stated are based on +20°C – the times will not be significantly extended at low temperatures.

Primary test data

Anti-skid

Tests carried out wet on new indicative samples in accordance with UKSRG Guidelines (2011). Based on HSE and UKSRG guidance a surface with a PTV of 36+ is classified as having a low slip potential.

Quartz Design

- With 0.7 1.2mm quartz:
 - PTV approx. 75 (Four S rubber / Slider 96)
 - PTV approx. 68 (TRRL rubber / Slider 55)
- With 0.4 1.2mm quartz:
 - PTV approx. 73 (Four S rubber / Slider 96)
 - PTV approx. 70 (TRRL rubber / Slider 55)
- With 0.4 0.8mm quartz:
 - PTV approx. 62 (Four S rubber / Slider 96)
 - PTV approx. 58 (TRRL rubber / Slider 55)
- With 0.3 0.6mm quartz:
 - PTV approx. 61 (Four S rubber / Slider 96)
 - PTV approx. 42 (TRRL rubber / Slider 55)

Colours and finishes

Available in a wide range of colours - refer to Triflex colour card.

Next steps

To ensure a thorough understanding of the construction, the substrate and to determine the most appropriate specification, Triflex carries out free of charge surveys, testing, investigations and analysis prior to preparing a bespoke project specification proposal. To arrange a meeting or site visit please contact Triflex Customer Services.

The advice we provide on the application of our products is based on extensive development work as well as many years of experience and is given to the best of our knowledge. However, the wide variety of requirements for a building under the most diverse conditions means that it is necessary for the Contractor to test the product for suitability in any given case. Triflex reserve the right to make alterations in keeping with technical developments or improvements.



Colour card Triflex ProDrain Quartz Design

Notes: There may be slight variations in shade between actual colours and those shown below. RAL colours are approximate.

Special colours can be produced to order.

Finish colours (including optional Triflex MicroChips): Triflex colours 2052 Amber 01 2053 Amber 02 1090 Amber 03 1091 Amber 04 7040 Slate 01 7037 Slate 02 7043 Slate 03 See. 8088 Marble 01 7087 Marble 02 7088 Marble 03 7089 Marble 04 5088 Azurite 01 5089 Azurite 02 5090 Azurite 03 9010 Sand 01 7090 Sand 02 8089 Sand 03 8090 Sand 04 7092 Granite 01 7093 Granite 02 7094 Granite 03 7095 Granite 04 6.7 2088 Agate 01 8091 Agate 02 8092 Agate 03 8054 Agate 04 5091 Opal 01 5092 Opal 02 5081 Opal 03 5094 Opal 04 100 8094 Garnet 01 8095 Garnet 02 8096 Garnet 03 7096 Malachite 01 7097 Malachite 02 7098 Malachite 03 7073 Malachite 04 10 8081 Ruby 01 3089 Ruby 02 3091 Ruby 04 3090 Ruby 03 6088 Jade 01 6089 Jade 02 6090 Jade 03 6091 Jade 04 7091 Amethyst 01 3092 Amethyst 02 4088 Amethyst 03 7035 Quartz 01 7032 Quartz 02 7030 Quartz 03 7034 Quartz 04 **RAL Greys** 7016 Anthracite grey 7030 Stone grey 7031 Blue grey 7032 Pebble grey 7035 Light grey 7037 Dusty grey 7043 Traffic grey 2 Quartz 03 Quartz 02 Quartz 01 Slate 02 Slate 03 **RAL Traffic** 4006 Traffic purple 1023 Traffic yellow 2009 Traffic orange 3020 Traffic red 5017 Traffic blue 6024 Traffic green 9005 Jet black 9010 Pure white

Request a sample online at triflex.co.uk/samplerequest

Find out more at triflex.co.uk



Colour card **Triflex ProDrain Colour Design**

Notes: There may be slight variations in shade between actual colours and those shown below.

Optional finish colours: Coloured surface dressing



A727 Creme Beige

A730 White

A721 Blue Grey



A720 Blue

Request a sample online at triflex.co.uk/samplerequest



Colour card Triflex ProDrain Chips Design

Notes: There may be slight variations in shade between actual colours and those shown below. RAL colours are approximate.

Special colours can be produced to order.

Optional finish colours: Triflex colours



Request a sample online at triflex.co.uk/samplerequest

Find out more at triflex.co.uk